

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Formula 570 Berry Dry

PRODUCT USE: Drying agent

MANUFACTURED FOR: Warsaw Chemical Holdings LLC.
P.O. Box 858
Warsaw, IN 46581

INFORMATION PHONE: Tel: 1-800-548-3396
Fax: 1-574-267-3884

EMERGENCY PHONE: INFOTRAC
1-800-535-5053 USA & Canada
352-323-3500 International

SECTION 2 - HAZARD(S) IDENTIFICATION

CLASSIFICATION: Acute Toxicity - Oral: Category 5
Eye Damage: Category 2A

PICTOGRAMS:



GHS ELEMENTS:

SIGNAL WORD: Warning

HAZARD STATEMENT(S): H303 | May be harmful if swallowed.
H319 | Causes serious eye irritation.

PRECAUTIONARY STATEMENT(S): P264 | Wash any exposed body parts thoroughly after handling.
P280 | Wear protective gloves/protective clothing/eye protection/face protection.
P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 | Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 | If eye irritation persists: Get medical advice/attention.

ADDITIONAL PRECAUTIONS: None Known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS #	PERCENT
2-Butoxyethanol	111-76-2	5 - 10%
SURFACTANT	Not Available	5 - 10%
Mineral Seal Oil	64742-46-7	1 - 5%
DAB SURFACTANT	Not Available	< 1.0%

PERFUME	Not Available	< 1.0%
Acetic Acid	64-19-7	< 1.0%
Proprietary Blend	Not Available	< 1.0%
Dye Basic Violet 10	81-88-9	< 1.0%
Nonylphenol ethoxylate	127087-87-0	< 1.0%

The chemical identity of some or all components is confidential business information (trade secret) and is being withheld as permitted by 29CFR19191200 (i). No other ingredients known to be hazardous.

SECTION 4 - FIRST AID MEASURES

EYES:	Check for and remove contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
SKIN:	Wash skin surfaces thoroughly after contact. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if irritation develops.
INHALATION:	Move exposed person to fresh air. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen clothing. Get medical attention immediately.
INGESTION:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
GENERAL:	Physicians: No specific treatment. Treat symptomatically. Contact poison treatment specialist if large quantities have been inhaled or ingested.

See Section 11 for exposure symptoms.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY:	In a fire or if heated, a pressure increase will occur and the container may burst.
EXTINGUISHING MEDIA:	Use an extinguishing agent suitable for the surrounding fire.
PROTECTIVE EQUIPMENT:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode.
ADDITIONAL INFORMATION:	Thermal decomposition products-carbon monoxide, sulfur oxides, metal oxide/oxides, halogenated compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	No action should be taken involving individual risk or without suitable training. Isolate area. Avoid contact with material. Do not breathe vapors. Provide adequate ventilation. Wear proper personal protective equipment.
-----------------------	--

ENVIRONMENTAL: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform relevant authorities if the product reaches sewers, waterways or soil.

CONTAINMENT/CLEANUP: Stop leak if without risk. Move containers from spill area. Contain or absorb with inert dry material. Dispose of according to local regulations. See Section 1 for emergency contact information and 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

SAFE HANDLING: Wear appropriate personal protective equipment (see Section 8). Eating drinking and smoking should be prohibited. Do not get into eyes or on skin. Do not ingest. Keep containers tightly closed. Do not reuse container.

SAFE STORAGE: Store in accordance with local regulations. Store in original container away from foods, drink and incompatible materials. Keep container tightly closed. Do not store unlabeled. Use appropriate containment.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Apply technical measures to comply with occupational exposure limits. Mechanical ventilation, eye-wash stations, showers where necessary.

EYE PROTECTION: Safety eye-wear/face shield complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

RESPIRATORY PROTECTION: Use a properly fitted air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates necessity. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product & the safe working limits of the chosen respirator.

HAND PROTECTION: Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

SKIN PROTECTION: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

COMPONENT	ACGIH TWA ppm	OSHA/NIOSH STEL ppm	OSHA/ACGIH STEL mg/m ³
2-Butoxyethanol	20.00	None	None
SURFACTANT	200.00	500.00	None
Mineral Seal Oil	5.00	None	None
DAB SURFACTANT	None	None	None
PERFUME	None	None	None
Acetic Acid	10.00	15.00	None
Proprietary Blend	None	None	None

Dye Basic Violet 10	None	None	None
Nonylphenol ethoxylate	10.00	None	None

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid	UPPER EXPLOSIVE LIMITS:	NA
COLOR:	Red	LOWER EXPLOSIVE LIMITS:	NA
ODOR:	Berry/Citrus	VAPOR PRESSURE:	NA
ODOR THRESHOLD:	NA	VAPOR DENSITY:	NA
PH:	NA	RELATIVE DENSITY:	NA
MELTING POINT:	NA	SOLUBILITY:	Water Soluble
FREEZING POINT:	NA	PARTITION COEFFICIENT:	NA
BOILING POINT:	NA	AUTO-IGNITION TEMPERATURE:	NA
FLASH PT METHOD:	NA	DECOMPOSITION TEMPERATURE:	NA
FLASH POINT:	NA	SPECIFIC GRAVITY:	0.97000
EVAPORATION RATE:	NA	% VOLATILE:	NA
FLAMMABILITY:	Nonflammable	VISCOSITY (cst):	NA

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY:	HAZARDOUS DECOMPOSITION PRODUCTS
CHEMICAL STABILITY:	Stable under normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS:	Reactive with metals.
CONDITIONS TO AVOID:	Avoid heat and open flames.
INCOMPATIBLE MATERIALS:	STRONG OXIDIZERS, ALKALIS - react with metals producing flammable hydrogen gas which can form explosive mixtures with air.
HAZARDOUS DECOMPOSITION PRODUCTS:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 - TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY:	Inhalation	Absorption	Ingestion
------------------	------------	------------	-----------

ACUTE EXPOSURE HAZARDS:

EYE CONTACT:	Severe eye irritation, burns.
DERMAL:	Skin irritation, can cause burns with contact.
ORAL:	Corrosive to mucous membranes.
INHALATION:	MIST MAY BE MILD TO STRONG IRRITANT, CORROSIVE.

2-Butoxyethanol (CAS No. 111-76-2)

Oral LD50: Rat 470 mg/kg

SURFACTANT (CAS No. Not Available)

Oral LD50: Rat 1000-2000 mg/kg

Mineral Seal Oil (CAS No. 64742-46-7)

Oral LD50: Rat >5000 mg/kg

DAB SURFACTANT (CAS No. Not Available)

Oral LD50: greater than 530mg/kg rat

Acetic Acid (CAS No. 64-19-7)

Oral LD50: 5000 mg/kg mice

Nonylphenol ethoxylate (CAS No. 127087-87-0)

Oral LD50: Rat 1600 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY:	No data available.
PERSISTENCE & DEGRADABILITY:	No data available.
BIOACCUMULATIVE POTENTIAL:	No data available.
MOBILITY IN SOIL:	No data available.
OTHER ADVERSE EFFECTS:	No data available.

2-Butoxyethanol (CAS No. 111-76-2)

Fish LC50: 1250mg/L, 96h, Inland Solverside

Crustacean LC50: Daphnia 1818 mg/L 24h

SURFACTANT (CAS No. Not Available)

Fish LC50: Flathead minnow 10000 mg/L 48h

Mineral Seal Oil (CAS No. 64742-46-7)

Fish LC50: 65 mg/L 96h, rainbow trout

DAB SURFACTANT (CAS No. Not Available)

Fish LC50: 1400mg//L 96h minnow

Acetic Acid (CAS No. 64-19-7)

Fish LC50: Rainbow trout 1000 mg/L

SECTION 13 - DISPOSAL CONSIDERATION

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility.

Processing, use or contamination of the product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

DOT (US)

UN NUMBER:	NA
SHIPPING NAME:	NA
TECHNICAL NAME:	NA
HAZARD CLASS:	NA
PACKAGING GROUP:	NA

SECTION 15 - REGULATORY INFORMATION

SARA 313 COMPONENTS	CAS NO.	% LESS THAN
2-Butoxyethanol	111-76-2	5 - 10%
SURFACTANT	Not Available	5 - 10%
CALIFORNIA PROP. 65 COMPONENTS	CAS NO.	% LESS THAN
2-Butoxyethanol	111-76-2	5 - 10%
SURFACTANT	Not Available	5 - 10%
Mineral Seal Oil	64742-46-7	1 - 5%
DAB SURFACTANT	Not Available	< 1.0%
Nonylphenol ethoxylate	127087-87-0	< 1.0%

This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm..

RTK: PA

California Prop 65

WARNING: This product can expose you to chemicals including Distillates (petroleum), hydrotreated middle, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

WARNING! This product contains a chemical known in the State of California to cause cancer: Coconut oil diethanolamide 5-10%

Component part, 1,2 propanediol (CAS# 57-55-6) PA and NJ RTK.

127087-87-0 Nonylphenol polyethylene glycol ether 90 - 100 %

25322-68-3 Polyethylene glycol 1 - 5 %

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

RTK: MA, PA, NJ,

WARNING! This product contains a chemical known to the State of California to cause cancer birth defects or other reproductive harm.

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

SECTION 16 - OTHER INFORMATION


HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	A

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

- A Safety Glasses
- B Safety Glasses, Gloves
- C Safety Glasses, Gloves, Apron
- D Face Shield, Gloves, Apron
- E Safety Glasses, Gloves, Dust Respirator
- F Safety Glasses, Gloves, Apron, Dust Respirator
- G Safety Glasses, Gloves, Vapor Respirator
- H Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- I Safety Glasses, Gloves, Dust & Vapor Respirator
- J Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- K Airline Hood or Mask, Gloves, Full Suit, Boots
- X Consult your supervisor for special handling directions

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)



NFPA warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals.

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information can be grounds for legal action.

To the best of our knowledge, the information provided in this Safety Data Sheet is accurate as of the date of its issue. However, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. The information this Safety Data Sheet contains is being given to that material when combined with other material(s) or when used otherwise than as described herein.

In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose. All materials may represent unknown hazards and should be used with caution.