

TECHNICAL DATA SHEET

CWS-17

FOAMING LOW PH PRESOAK

OVERVIEW

An ultra-concentrated, high-foaming, acid-based presoak that penetrates and removes road film, oil, grease, and dirt from the vehicle surface. Use to prep and clean the vehicle surface before applying a high pH presoak. Combining both products helps you overcome poor cleaning conditions.

FEATURES

- Foamy application for excellent customer appeal
- Helps with challenging cleaning issues
- Safer than most low pH presoaks
- Safe to use on any vehicle surface

APPLICATION

- Tunnel & rollover
- APPROXIMATE USAGE: 20–45 mL/CAR
120:1–240:1
- For best results apply before a high pH presoak
- Use proportioner tips (i.e. HydroMinder, Dema, etc.) in conjunction with downstream injection (i.e. Dema, venturi, etc.) to achieve final use dilution.



PACKAGING

5, 30 & 55 USG

PHYSICAL CHARACTERISTICS

Ultra-Concentrated

pH (100%): < 2

SG: 1.05

TITRTION

Amount: 10ml

Reagent: 0.2N NaOH

Dilution - Drops

80:1 - 26

100:1 - 21

120:1 - 19

140:1 - 16

160:1 - 15

180:1 - 13

200:1 - 12

220:1 - 9

240:1 - 9

**REFER TO SAFETY DATA
SHEET FOR EMERGENCY
MEDICAL INFORMATION**