

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : BLUE CORAL POLYBOND WAX

Material number : 000000000007600148

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

#### Emergency telephone numbers

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

|            |            |
|------------|------------|
| Appearance | liquid     |
| Colour     | yellow     |
| Odour      | like fruit |

#### GHS Classification

Flammable liquids : Category 3  
Skin corrosion : Category 1B  
Serious eye damage : Category 1  
Skin sensitisation : Category 1  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Flame



Health hazard



Corrosion



Exclamation  
mark

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

| Chemical name                                                  | CAS-No.    | Concentration [%] |
|----------------------------------------------------------------|------------|-------------------|
| Distillates (petroleum), hydrotreated middle                   | 64742-46-7 | >= 20 - < 30      |
| Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides | 61789-77-3 | >= 5 - < 10       |
| d-limonene                                                     | 5989-27-5  | >= 3 - < 5        |
| propan-2-ol                                                    | 67-63-0    | >= 1 - < 3        |

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

|                                                                                                                           |            |                |
|---------------------------------------------------------------------------------------------------------------------------|------------|----------------|
| Amines, tallow alkyl, ethoxylated                                                                                         | 61791-26-2 | $\geq 1 - < 3$ |
| Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides                                  | 61791-10-4 | $\geq 1 - < 3$ |
| Fatty acids, coco, reaction products with diethylenetriamine and soya fatty acids, ethoxylated, chloromethane-quaternized | 68604-75-1 | $\geq 1 - < 3$ |

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Get medical attention immediately.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
Wash off immediately with plenty of water for at least 15 minutes.  
Remove contaminated clothing and shoes.  
Wash contaminated clothing before reuse.  
If skin irritation persists, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.  
Effects are immediate and delayed.  
Symptoms may include blistering, irritation, burns, and pain.  
Effects are dependent on exposure (dose, concentration, contact time).  
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.  
Causes severe skin burns and eye damage.  
May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

May cause an allergic skin reaction.  
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

- |                                               |                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                  | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical                                                                                                                                                                                                                                             |
| Unsuitable extinguishing media                | : High volume water jet                                                                                                                                                                                                                                                                                                   |
| Specific hazards during firefighting          | : Do not allow run-off from fire fighting to enter drains or water courses.                                                                                                                                                                                                                                               |
| Hazardous combustion products                 | : Carbon dioxide (CO <sub>2</sub> )<br>Carbon monoxide<br>Smoke<br>Nitrogen oxides (NO <sub>x</sub> )<br>Chlorine compounds                                                                                                                                                                                               |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                                                                                                                                 |
| Further information                           | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>Use a water spray to cool fully closed containers.<br>Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.                                                                                                                                                                                                                                                  |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |                                                                     |                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions                                           | : Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains, inform respective authorities.                                                            |
| Methods and materials for containment and cleaning up               | : Neutralise with acid.<br>Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to                                           |

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store near acids.  
Oxidizing agents
- Storage temperature : 0 - 50 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components  | CAS-No.   | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis     |
|-------------|-----------|----------------------------------|---------------------------------------------------|-----------|
| d-limonene  | 5989-27-5 | TWA                              | 30 ppm                                            | US WEEL   |
| propan-2-ol | 67-63-0   | TWA                              | 200 ppm                                           | ACGIH     |
|             |           | STEL                             | 400 ppm                                           | ACGIH     |
|             |           | TWA                              | 400 ppm<br>980 mg/m3                              | NIOSH REL |
|             |           | ST                               | 500 ppm<br>1,225 mg/m3                            | NIOSH REL |
|             |           | TWA                              | 400 ppm                                           | OSHA Z-1  |

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

|  |  |      |                        |         |
|--|--|------|------------------------|---------|
|  |  |      | 980 mg/m3              |         |
|  |  | TWA  | 400 ppm<br>980 mg/m3   | OSHA P0 |
|  |  | STEL | 500 ppm<br>1,225 mg/m3 | OSHA P0 |
|  |  | PEL  | 400 ppm<br>980 mg/m3   | CAL PEL |
|  |  | STEL | 500 ppm<br>1,225 mg/m3 | CAL PEL |

### Biological occupational exposure limits

| Component   | CAS-No. | Control parameters | Biological specimen | Sampling time                   | Permissible concentration | Basis     |
|-------------|---------|--------------------|---------------------|---------------------------------|---------------------------|-----------|
| PROPAN-2-OL | 67-63-0 | Acetone            | Urine               | End of shift at end of workweek | 40 mg/l                   | ACGIH BEI |

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: yellow

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

|                                        |                               |
|----------------------------------------|-------------------------------|
| Odour                                  | : like fruit                  |
| Odour Threshold                        | : No data available           |
| pH                                     | : 10                          |
| Melting point/freezing point           | : No data available           |
| Boiling point                          | : No data available           |
| Flash point                            | : 43 °C<br>Method: closed cup |
| Evaporation rate                       | : No data available           |
| Upper explosion limit                  | : No data available           |
| Lower explosion limit                  | : No data available           |
| Vapour pressure                        | : No data available           |
| Relative vapour density                | : No data available           |
| Relative density                       | : 0.95                        |
| Density                                | : 0.95 g/cm <sup>3</sup>      |
| Solubility(ies)                        |                               |
| Water solubility                       | : Not applicable              |
| Solubility in other solvents           | : Not applicable              |
| Partition coefficient: n-octanol/water | : No data available           |
| Auto-ignition temperature              | : not determined              |
| Thermal decomposition                  | : No data available           |
| Viscosity                              |                               |
| Viscosity, kinematic                   | : No data available           |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                                       |
|------------------------------------|-------------------------------------------------------------------------------------------------------|
| Reactivity                         | : Stable                                                                                              |
| Chemical stability                 | : Stable under normal conditions.                                                                     |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air.<br>No decomposition if stored and applied as directed. |
| Conditions to avoid                | : Heat, flames and sparks.                                                                            |
| Incompatible materials             | : Acids<br>Oxidizing agents                                                                           |
| Hazardous decomposition products   | : Carbon dioxide (CO <sub>2</sub> )<br>Carbon monoxide<br>Halogenated compounds                       |

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

Nitrogen oxides (NOx)

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Aspiration may cause pulmonary oedema and pneumonitis. Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration, contact time). Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat. Causes severe skin burns and eye damage. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : 4,863 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

### Components:

#### **d-limonene:**

Acute oral toxicity : LD50 Oral Rat: 4,400 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 5,000 mg/kg

#### **propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg  
Method: Calculation method

### **Skin corrosion/irritation**

#### Product:

Remarks: Extremely corrosive and destructive to tissue.

### **Serious eye damage/eye irritation**

#### Product:

Remarks: May cause irreversible eye damage.

### **Respiratory or skin sensitisation**

#### Product:

Remarks: Causes sensitisation.

### Components:

#### **d-limonene:**

Classification: May cause sensitisation by skin contact.

### **Germ cell mutagenicity**

No data available

### **Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **STOT - single exposure**

No data available

### **STOT - repeated exposure**

No data available

### **Aspiration toxicity**

No data available

### **Further information**

#### Product:

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

Remarks: Solvents may degrease the skin.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

##### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

##### Components:

##### **d-limonene :**

Partition coefficient: n-octanol/water : log Pow: 4.232

##### **propan-2-ol :**

Partition coefficient: n-octanol/water : log Pow: 0.05

#### Mobility in soil

No data available

#### Other adverse effects

No data available

##### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Not applicable

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):  
UN1993, FLAMMABLE LIQUID, N.O.S., (ISOPROPANOL), 3, III

Transportation Regulation: IATA (Cargo Air):  
UN1993, Flammable liquid, n.o.s., (ISOPROPANOL), 3, III

Transportation Regulation: IATA (Passenger Air):  
UN1993, Flammable liquid, n.o.s., (ISOPROPANOL), 3, III

Transportation Regulation: TDG (Canada):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

| Components    | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------|---------|--------------------|-----------------------------|
| chloromethane | 74-87-3 | 100                | *                           |

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

| Components      | CAS-No.  | Component RQ<br>(lbs) | Calculated product RQ<br>(lbs) |
|-----------------|----------|-----------------------|--------------------------------|
| 2-chloroethanol | 107-07-3 | 500                   | *                              |

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitisation  
Aspiration hazard

**SARA 302** : The following components are subject to reporting levels established by SARA Title III, Section 302:  
2-chloroethanol 107-07-3 0.1 %

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop. 65**



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, ethylene oxide, 1,4-dioxane, methyloxirane, which is/are known to the State of California to cause cancer, and chloromethane, ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

---

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

### Further information

#### NFPA:

|                 |   |
|-----------------|---|
| HEALTH          | 3 |
| FLAMMABILITY    | 2 |
| INSTABILITY     | 0 |
| SPECIAL HAZARD. |   |

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

|                 |    |
|-----------------|----|
| HEALTH          | 3* |
| FLAMMABILITY    | 2  |
| PHYSICAL HAZARD | 0  |

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Danger:**  
: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. May cause an allergic skin reaction.  
: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

# SAFETY DATA SHEET

## BLUE CORAL POLYBOND WAX

Version 2.1

Revision Date 06/09/2020

Print Date 04/27/2021

POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents/container in accordance with local regulation.

|                |            |
|----------------|------------|
| Version:       | 2.1        |
| Revision Date: | 06/09/2020 |
| Print Date:    | 04/27/2021 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.